

PREMIUM PR

TM



		75g/m ²	80g/m ²	90g/m ²	100g/m ²	120g/m ²	
PRE-PRINT	Whiteness CIE	ISO 11475	169	169	169	169	
	Opacity %	ISO 2471	93	95	96	97	
	Moisture %	ISO 287	5,0	5,0	5,0	5,2	
	Bendtsen Roughness ml/min	ISO 879/2	180	150	150	100	
	Thickness μm	ISO 534	103	108	114	118	
	Bulk μm/g/m ²	-	1,37	1,35	1,27	1,18	
	Certified	FSC® ⁽¹⁾	✓	✓	✓	✓	✓
	Awarded by	Eco-label ⁽²⁾	✓	✓	✓	✓	✓

MAY 2016

Pre-Print Folio

Technical References - Targets only, without tolerances mentioned
Basis weight g/m² - ISO 536

Additional Information about The Navigator Company, Mills and Products:

The Navigator Company mills are chain-of-custody certified by NepCon in accordance with FSC-STD-40-004 (NC-COC-001829) and FSC-STD-40-005 (NC-CW-001829). In accordance with the requirements of ISO 9706 standard Elemental Chlorine Free (ECF)
Quality Management Systems Standard ISO 9001
Environmental Management Systems Standard ISO 14001
Occupational Health and Safety Management Systems Standard OHSAS 18001

